

Tech Specs

UniFi UISP Branding

60 GHz Wireless Wireless Fiber Wired Accessory Tech

Wireless / airMAX Rocket M3

Datasheet Marketing Images

Mechanical

Dimensions 160 x 80 x 30 mm (6.3 x 3.15 x 1.18")

Weight 500 g (1.1 lb)

Enclosure material UV-stabilized plastic

Hardware

Networking interface (1) 10/100 MbE RJ45 port

Power method Passive PoE (pairs 4, 5+; 7, 8 return)

Power supply 24V, 1A PoE adapter (Included)

Max. power consumption 6.5W

RF connectors (2) RP-SMA (waterproof)

Operating frequency 3400 - 3730 MHz*

*RocketM3 not supported in the USA.

Shock and vibration ETSI300-019-1.4

Operating temperature -30 to 75° C (-22 to 167° F)

Operating humidity 5 to 95% noncondensing

Certifications CE, FCC, IC

Software

Operating mode Access Point, station

Software management Bluetooth management for easy setup over UISP Mobile app

WEB L

Minimum software requirements Any modern web browser/iOS™ or Android™ based smartphone

Security WPA2 AES only

Services Services web server, SNMP, SSH server, telnet , ping watchdog, DHCP, NAT, bridging, routing

Utilities Antenna alignment tool, discovery utility, site survey, ping, traceroute, speed test

QoS Supports packet level classification WMM and user customer level: High/Medium/Low

	Stay in Touch							
	Email					Subscribe		
		f	y		0			
Terms and Cond	ditions Terms of	f Service	Priva	acy Policy	/ R	eturn Policy (Cookies Setting	gs

© 2023 Ubiquiti, Inc. All rights reserved.