

Tech Specs

UniFi UISP Branding

[UniFi Cloud Gateways](#) [WiFi](#) [Switching](#) [Cloud Keys & Gateways](#) [Camera Security](#) [Door Access](#) [Phone System](#) [New Integrations](#) [Accessories](#)

[Accessories](#) / 1 Gbps Bidirectional Single-Mode Optical Module


[Datasheet](#)

[Marketing Images](#)

UACC-OM-SM-1G-S

Supported Media	Single-Mode Fiber
Connector Type	(1) LC
BiDi	Yes
TX Wavelength*	Blue Latch: 1310 nm Yellow Latch: 1550 nm Must be used in pairs (blue latch and yellow latch).
RX Wavelength*	Blue Latch: 1550 nm Yellow Latch: 1310 nm Must be used in pairs (blue latch and yellow latch).
Data Rate	1.25 Gbps
Max. Power Consumption	0.66W
Cable Distance	3 km
Operating Temperature	0 to 70° C (32 to 158° F)
Pack Options	2-pack, 20-pack
WARNING	CLASS 1 LASER PRODUCT, IEC/EN 60825-1:2014 – Do not look into the ends of the fiber optic cable or SFP module while converters are powered.

Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2023 Ubiquiti, Inc. All rights reserved.