

Q UA-Button

Switching

WiFi

Camera Security

Door Access

Integrations

Advanced Hosting

For Door Access > [Access Button](#)

Datasheet

In The Box

Marketing Images

Installation Guide

Mechanical

Dimensions	137 x 88 x 38.1 mm (5.4 x 3.5 x 1.5")
Weight	180 g (6.3 oz)
Enclosure material	Polycarbonate
Mounting material	Metal
Color	Black/white

Hardware

Contact type	(1) Normal open
Power method	UniFi Access Hubs UL 294 Power-limited Class 2 PSU UL 60950-1/62368-1 LPS/PS2 PSU
Contact rating	30V DC, 2A
Mechanical life	1,000,000 clicks
Environment	Indoor only
Storage temperature	-40 to 70° C (-40 to 158° F)
Ambient operating temperature	0 to 40° C (32 to 104° F)
Ambient operating humidity	5 to 90% noncondensing

UL 294 level	Destructive attack: Level I Line security: Level I Endurance: Level I Standby power: Level I
UL 294 statement	Compliance with IEEE 802.3 (at or af) specifications was not verified as part of UL 294. The equipment is intended to comply with the section of the National Electrical Code, ANSI/NFPA 70, Article 725.121, Power Sources for Class 2 and Class 3 Circuits.
CAN/ULC-60839-11-1 Grade	Grade assignment: 1
Certification	CE, UL 294, CAN/ULC-60839-11-1
Document number, and issue date and/or revision level	UA-Button, V01

Stay in Touch

 

[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2025 Ubiquiti, Inc. All rights reserved.