

Search UniFi products

- Cloud Gateways
- Switching
- WiFi
- Camera Security
- Door Access
- Integrations
- Advanced Hosting
- Accessories

Readers > [G6 Entry](#)



G6 Entry UVC-G6-Entry

Datasheet

- In The Box
- Marketing Images
- Installation Guide



Overview


Dimensions	176 x 45 x 29.6 mm (6.9 x 1.8 x 1.2")
IR Night Vision	5 m (16 ft)
Face Recognition	✓
Smart Detections (People, Vehicles, Animals)	✓
Resolution	Main camera: 5MP Package camera: 8MP
Field of View	Main camera: H: 100°, V: 135°, D: 180° Package camera: H: 66°, V: 51.7°, D: 78°
Audio	Two-way audio
Weatherproofing	IP55
Tamper Resistance	IK07
Mounting	Wall mount, Gangbox mount plate, 20° wedge mount (Included) Junction box (Optional)
NFC Card & Keyfob Access	✓
Apple/Google Wallet	✓
Face Unlock	✓
Mobile Unlock	✓
Two-Way Intercom & Doorbell Access	✓

Performance

Networking Interface	GbE RJ45 port
Connectivity	BLE 4.1 NFC

Video	
Image Settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay, HDR
Max. Frame Rate	Main camera: 30 FPS Package camera: 3 FPS
Resolution	Main camera: 5MP, 1920 x 2560 (3:4) Package camera: 8MP 3264 x 2448 (4:3)
Optics	
Sensor	Main camera: 5MP CMOS Package camera: 8MP CMOS
Lens	Fixed focal length
Night Mode	Built-in IR LED illumination and IR cut filter
^ Hardware	
Max. Power Consumption	16W
Supported Voltage Range	42—57V DC
Power Method	PoE+
Processor	Quad-core Arm® Cortex®-A53 based chip
Weight	275 g (9.7 oz)
Enclosure Material	Aluminum
Mount Material	Wall mount: Stainless steel Gangbox mount plate: SGCC steel Gangbox mount cover: Polycarbonate Wedge mount: Aluminum
Button	(1) Ring button (1) Factory-reset (1) Tamper switch
LEDs	R/G/B/W Learn More
Ambient Operating Temperature	-30 to 50° C (-22 to 122° F)
Ambient Operating Humidity	5 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC

Stay in Touch



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2026 Ubiquiti, Inc. All rights reserved.